

1. Description

The Everlux adhesive is a synthetic rubber solution, easily extrusive, of easy and clean fixing and which dries quickly. It shows a high resistance to pulling off and to humidity and allows it to be glued to irregular surfaces. This glue was especially developed for the best fixing of the Everlux signs without requiring screws or nails. Tests show that it provides the best adherence to most surfaces where signs are fixed.

2. Characteristics

• Aspect:	Homogeneous paste.
• Viscosity:	Easily extrusive paste
• gluing time:	Immediate or up to 10 minutes.
• Time to stick:	Definitive after 24 hours.
• Minimum Temperature of fixing :	+5 ° C
• Resistance to temperature:	-20 °C to 100 °C
• Application temperature:	+5 °C to 50°C
• Flammable point:	-4° C
• Resistance to slippage (according to NF P 85501):	0 mm (non-slip)
• Resistance to traction:	35 Kg/sqcm
• Cleaning:	Easily removed with alcohol

3. Directions to use

- The temperature for fixing must be between 5 °C and 50 °C.
- The signs and the surfaces where they are going to be applied must be dry and with no dust, mud, oil or grease.
- Apply the Everlux adhesive using a manual or pneumatic pistol
- Apply a 5mm non continuous string of the adhesive at approximately 1cm of the edge in the rear face of the sign. Alternatively, small adhesive dots can also be applied.
- Complete the process by pressing on the sign against the wall/surface in order to squeeze and to get an even distribution of the adhesive. To get a better installation result, paste the sign to the wall/ surface and remove it immediately in order to get the adhesive slightly dried before proceeding with the definitive installation.
- There is 5 minutes in which to put the sign in its final position.
- the Everlux adhesive allows a correction on the irregularities of the surfaces where it is applied up to 5mm.

4. Packaging and spread

Cartridge of 300 ml

Considering a line of 5mm diameter, approximately 15 metres long, which means:
25 small signs (15x20 cm); 15 medium signs (20x30 cm); 10 big signs (40x60 cm)

5. Storage and time it lasts

Store between 5 °C and 35 °C in a dry, fresh and well ventilated place in its unopened original packaging. Away from heat and direct sunlight. Keep away from ignition points.

To be used within 36 months after the manufacturing date shown in the tube. After this period, the adhesive keeps all of its properties if the tube is kept sealed and stored under the indicated conditions.

6. Hygiene and Safety

Easily flammable and irritating to the skin.

Do not smoke or use open flame near the work zone. Wear gloves and in the case of staining, wash with a industrial detergent while the product is still fresh.

NOT TO WASH HANDS WITH SOLVENTS.

Toxic for aquatic organisms.

For further information, please consult the relative Safety Data Sheet.